



IGWX E2

$U_w = 1,2 \text{ W/m}^2\text{K}^*$

GLAZING UNIT


$U_g = 1,0 \text{ W/m}^2\text{K}$



GLAZING UNIT

double glazing

- gas - argon
- warm spacer
- low emission coat
- toughened pane



4H/16/4T (AR)
 $U_g = 1,0 \text{ W/m}^2\text{K}$

PRODUCT CHARACTERISTICS

- ✓ window with joinery made of multi-chamber PVC profiles
- ✓ profile chambers are filled with insulating material and reinforced with steel cores, which significantly increases the insulation parameters of the window
- ✓ the profile is resistant to moisture and requires no maintenance
- ✓ the window is easy to keep clean
- ✓ carpentry color - aesthetic white
- ✓ the window is extremely tight thanks to 4 seals
- ✓ safe handle with a key and a micro-opening function
- ✓ fashionable color of the flashing - RAL 7016
- ✓ wide range of installation angle 15-65°
- ✓ skylight for non-habitable areas
- ✓ can be installed with additional sealing accessories
- ✓ wide range of internal blinds and pleats



GUARANTEE

- ✓ 2 years guarantee (detailed conditions are available on the website www.okpol.pl)



30°



180°

AVAILABLE SIZES

Glazing area [m ²]	0,23
Symbol size	01
Window sizes: width x height [cm]	55x78

*Parametr U_w - współczynnik przenikalności cieplnej okienpodano dla rozmiarów referencyjnych 1,23 (±25%)m x 1,48 (-25%)m, obliczenia wg norm EN ISO 10077-1 / EN ISO 10077-2