



# IGWX+ E2

Uw = 1,2 W/m<sup>2</sup>K\*

GLAZING UNIT

Ug = 1,0 W/m<sup>2</sup>K




Integrated underfelt collar improves connection with existing roofing felt

## GLAZING UNIT

double glazing

- gas - argon
- warm spacer
- low emission coat
- toughened pane



4H/16/4T (AR)  
Ug = 1,0 W/m<sup>2</sup>K

## PRODUCT CHARACTERISTICS

- ✓ window with joinery made of multi-chamber PVC profiles
- ✓ profile chambers are filled with insulating material
- ✓ and reinforced with steel cores, which significantly increases the insulation parameters of the window
- ✓ the profile is resistant to moisture and requires no maintenance
- ✓ the window is easy to keep clean
- ✓ carpentry color - aesthetic white
- ✓ the window is extremely tight thanks to 4 seals
- ✓ safe handle with a key and a micro-opening function
- ✓ fashionable color of the flashing - RAL 7016
- ✓ wide range of installation angle 15-65°
- ✓ gas springs to facilitate the ease of opening up to 30°
- ✓ skylight for non-habitable areas
- ✓ can be installed with additional sealing accessories
- ✓ wide range of internal blinds and pleats



## GUARANTEE

- ✓ 2 years guarantee (detailed conditions are available on the website [www.okpol.pl](http://www.okpol.pl))



## AVAILABLE SIZES

Glazing area [m <sup>2</sup> ]	0.23	0.30	0.40	0.48
Symbol size	01	02	03	05
Window sizes: width x height [cm]	55x78	55x98	66x98	78x98



30°



180°

\*Parametr Uw - współczynnik przenikalności cieplnej okienpodano dla rozmiarów referencyjnych 1,23 (±25%)m x 1,48 (-25%)m, obliczenia wg norm EN ISO 10077-1 / EN ISO 10077-2