



ISOV E2

Uw = 1,2 W/m²K

GLAZING

Ug = 1,0 W/m²K

10 years
*
GUARANTEE
FOR WINDOWS

5 years
*
GUARANTEE
FOR GLASS



GLAZING

double glazed unit
gas - argon
warm spacer
low emission coat
toughened pane

4 Gaskets

Handle with the lock
and micro-ventilation
(2 keys in a set)

NEO-VENT air inlet

Impregnated pine wood

Roof pitch

Non-standard sizes
55-134cm × 78-160cm

The non-standard orders are can be completed after a consultation with technical sales advisor or customer service office.



Window sizes:

| glazing area [m ²] | 0.20 | 0.27 | 0.36 | 0.45 | 0.55 | 0.45 | 0.56 | 0.70 | 0.81 | 0.71 | 0.89 | 1.04 | 0.91 | 1.12 | 0.88 |
|----------------------------------|-------|-------|-------|--------|--------|-------|--------|--------|--------|--------|--------|--------|---------|---------|--------|
| size symbol | 01 | 02 | 03 | 04 | 15 | 05 | 06 | 07 | 13 | 08 | 09 | 14 | 10 | 11 | 12 |
| window size: width × height [cm] | 55×78 | 55×98 | 66×98 | 66×118 | 66×140 | 78×98 | 78×118 | 78×140 | 78×160 | 94×118 | 94×140 | 94×160 | 114×118 | 114×140 | 134×98 |
| ISOV E2 | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |

*Details about the guarantee policy available at www.okpol.com

Windows may be used in buildings for which building permits have been issued or submitted by the end of 2020. Roof windows with the Uw ≤ 1.3 W / m²K parameter can still be used in rooms with a temperature of ≥ 16 ° C.