



ISOV I25

Uw = 1,06 W/m²K*

GLAZING

Ug = 0,7 W/m²K


10 years
*
GUARANTEE
FOR WINDOWS

5 years
*
GUARANTEE
FOR GLASS



GLAZING

triple glazed unit
gas - argon
2 x warm spacer
2 x low emission coat
toughened external pane
safety glass P2A



4H/12/4TH/10/33.2T

4 gaskets

handle with the lock
and micro-ventilation
(2 keys in set)

NEO-VENT air inlet

Impregnated pine wood

Roof pitch



Non standard sizes
55-134cm × 78-160cm

The non-standard orders can be completed after a consultation with technical sales advisor or customer service office.



Window sizes:

glazing area [m ²]	0.20	0.27	0.36	0.45	0.55	0.45	0.56	0.70	1.13	0.71	0.89	1.04	0.91	1.12	0.88
size symbol	01	02	03	04	15	05	06	07	13	08	09	14	10	11	12
window size: width × height [cm]	55×78	55×98	66×98	66×118	66×140	78×98	78×118	78×140	78×160	94×118	94×140	94×160	114×118	114×140	134×98
ISOV I25	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

*Parameter Uw - thermal permeability coefficient.

**Details about the guarantee policy available at www.okpol.com